





## Three different types of skip mean even greater utility - 1601.


Even greater utility for building processes, logistics and environmental technology: The standard front-tipping skip is ideal for fast material turnover. The high-tipping skip bridges differences in height. The swivel-tipping skip with its 180-degree tilt dumps the material precisely where it is needed.

- Three different types of skip: Front-tipping skip (standard); high-tipping skip and optional swivel tipping skip, maximum payload 1,500 kg.
- Hydrostatic twin-lock all-wheel drive.
- Continuously variable speed up to 16 km/h max.
- Large service and maintenance access.
- Clearly laid out instrument panel and wide, robust leg protection.

## **1601 Technical specifications**

	Front tip skip	Swivel tip skip	High tip skip
Operating data			
Payload kg	1,500	1,500	1,500
Shipping weight kg	1,261	1,261	1,261
Skip capacity level I	829	650	650
Skip capacity heaped I	1,044	800	800
Skip capacity water level I	612	325	420
Engine / Motor			
Engine / Motor manufacturer	Yanmar	Yanmar	Yanmar
Engine / Motor type	3TNV76	3TNV76	3TNV76
Engine / Motor	Diesel	Diesel	Diesel
Engine performance acc. to ISO 3046/1 kW	17	17	17
Displacement cm <sup>3</sup>	1,116	1,116	1,116
Engine RPM rpm	3000	3000	3000
Travel speed km/h	16	16	16
Articulation angle °	33	33	33
Pendulum angle °	15	15	15
Turning radius mm	3,300	3,300	3,300
Gradeability %	50	50	50
Tires	10.00/75-15	10.00/75-15	10.00/75-15
LxWxH mm	3310 x 1310 x 2550	3220 x 1310 x 2550	3300 x 1310 x 2550
Steering pump	Axial piston pump	Axial piston pump	Axial piston pump
Flow rate I/min	84	84	84
Operating pressure bar	420	420	420
Duty pump	Gear pump	Gear pump	Gear pump
Flow rate I/min	25	25	25
Operating pressure bar	170	170	170
Fuel tank capacity I	20	20	20
Sound level (LwA) dB(A)	101	101	101

## **1601 Dimensions**



		Front tip skip	Swivel tip skip	High tip skip
A	Overall length	3,310 mm	3,220 mm	3,300 mm
В	Wheelbase	1,700 mm	1,700 mm	1,650 mm
С	Rear overhang	810 mm	810 mm	810 mm
D	Height			1,885 mm
E	Dumping distance	370 mm	280 mm	400 mm
F	Width vehicle	1,305 mm	1,305 mm	1,305 mm
G	Skip width	1,300 mm	1,260 mm	1,200 mm
Н	Height ROPS	2,550 mm	2,550 mm	2,550 mm
ı	Height ROPS tipped	1,960 mm	2,000 mm	2,000 mm
K	Dump height max.	360 mm	705 mm	370 mm
K	Dump height max. High tip skip raised			1,600 mm
L	Skip height gekippt	1,970 mm	2,240 mm	1,895 mm
L	Skip height High tip skip raised			2,975 mm
М	Skip height	1,345 mm	1,310 mm	1,345 mm
N	Dumping distance lateral		100 mm	
0	Ground clearance	260 mm	270 mm	270 mm
Q	Distance	460 mm		390 mm

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations. Copyright © 2019 Wacker Neuson SE.