
Bergmann Dumper







- High stability thanks to oscillating axle
- Swivelling operator's stand
- > Electro hydraulic spring type cylinder park brake
- Compact dimensions and low weight





3012 R_{PLUS} **Technical Data**



Weight/Bucket Capacity

	payload	12.000 kg
	empty weight	11.140 kg
	loading capacity struck	6,3 m ³
	loading capacity heaped	8,0 m ³
	bucket system	hydraulical swivel tip
Dimensions		
	clearance height	3.022 mm
	tipping height	1.344 mm
	loading height (front)	2.408 mm
	total length	7.129 mm
	total width	
	ground clearance	429 mm
Transmission		
	load-depending shift – manually shiftable by hand a and speed, speed control stepless forward and back	and automatically, self-adjusting optimisation of traction force wards, ZF-Ergo-Power transmission
	1. gear f/b	6/6 km/h
	2. gear f/b	9/15 km/h
	3. gear f/b	14/33 km/h
	4. gear f	21 km/h
	5. gear f	32 km/h
	6. gear f	40 km/h
Steering		
	hydraulical articulated steering acting over prior articulation: 37° left & right	rity valve
Axles/Brakes		
		-free-oil-bath multi-disc brake in the wheel hubs with self- hydraulically applicated spring-type cylinder locking brake de
Engine		
	4 cylinder Cummins diesel engine – water coole power 119 kW with 2.200 rpm Tier IV Interim	d –
Tvres		
	standard 20.5-25 double coin	
Bonnet		
	easy access to all maintenance and service point	ts thanks to wide opening sectioned bonnet
Tank Capacity		and the step of th
	fuel	190 L
	hydraulic oil	
Electrics		
	24.V electric system with main switch fault findi	ng modus, fuel and hour counter, control lamps for engine
	-	control, hydraulic filter, display for drive position
Standard Equipment		
	according to German traffic regulations, hardox p	er's seat, swivelling operator's stand, lighting system plates in the bucket, flashing yellow light, cigarette lighter,
	roller blind for front windscreen, device for radio,	loudspeaker and antenna, EC declaration of conformity

