

| BALE   | 623 Silage/Multicrop                       |                     | 644                                   |                                       | 644 Premium           |
|--|--|---------------------|---------------------------------------|---------------------------------------|-----------------------|
| Diameter (m)   | 1.25 – 1.35                                | 1.25 – 1.35         | 1.25 – 1.35                           | 1.25 – 1.35                           | 1.25 – 1.35           |
| Width (m)  | 1.17                                       | 1.17                | 1.17                                  | 1.17                                  | 1.17                  |
| Volume (m <sup>3</sup> )                                   | 1.34                                       | 1.34                | 1.34                                  | 1.34                                  | 1.34                  |
| <b>PICK-UP</b>   | 2 m RotoFlow                               | 2 m MaxiCut 14      | 2 m MaxiCut 14                        | 2.2 m MaxiCut 14                      | 2.2 m MaxiCut 25      |
| Outer width (m, between flares)                            | 2  | 2                   | 2                                     | 2.2                                   | 2.2                   |
| Power Requirements (kW/hp)                                 | 60/80                                      | 67/90               | 75/100                                | 75/100                                | 89/120                |
| Roller Baffle  | –  | –                   | Option                                | Option                                | Base                  |
| Standard gauge wheels                                      | Base                                       | Base                | Base                                  | Base                                  | Base                  |
| Pivoting gauge wheels                                      | –  | –                   | Option                                | Option                                | Option                |
| <b>FEEDING SYSTEM</b>                                      |  |                     |                                       |                                       |                       |
| Precutter  | None –RotoFlow                             | 14 Knives           | 14 Knives                             | 14 Knives                             | 25 Knives             |
| Minimum theoretical Cutting length (mm)                    | –  | 70                  | 70                                    | 70                                    | 40                    |
| Knife selection  | –  | –                   | Option 0, 7, 7, 14                    | Option 0, 7, 7, 14                    | Base 0, 7, 12, 13, 25 |
| Unplugging device  | Pivoting drop floor                        | Pivoting drop floor | Pivoting drop floor                   | Pivoting drop floor                   | Pivoting drop floor   |
| <b>BALE CHAMBER</b>  |  |                     |                                       |                                       |                       |
| Type   | Multicrop: 7 rolls + chain & slat conveyor | Silage: 17 Rolls    | 17 rolls                              | 17 rolls                              | 17 rolls              |
| Automatic drive chain lubrication                          | Base                                       | Base                | Base                                  | Base                                  | Base                  |
| Central greasing banks                                     | –  | –                   | Base                                  | Base                                  | Base                  |
| <b>BALE CHAMBER DRIVE</b>                                  |  |                     |                                       |                                       |                       |
| 540 rpm @ 2000 N.m   | Base                                       | Base                | Base                                  | Base                                  | –                     |
| 1000 rpm @ 1300 N.m  | –  | –                   | Option                                | Option                                | Base                  |
| Powerdrive increased greasing interval PTO                 | –  | –                   | X only w/ 1000 rpm @ 1300 N.m gearbox | X only w/ 1000 rpm @ 1300 N.m gearbox | Base                  |
| <b>TWINE BINDING SYSTEM</b>                                |  |                     |                                       |                                       |                       |
| Type   | Two arms                                   | Two arms            | Two arms                              | Two arms                              | Two arms              |
| Storage 10 twine balls                                     | –  | –                   | Option                                | Option                                | Option                |
| <b>NETWRAP</b>   |  |                     |                                       |                                       |                       |
| Type   | CoverEdge                                  | CoverEdge           | CoverEdge                             | CoverEdge                             | CoverEdge             |
| <b>BALE UNLOADING</b>                                      |  |                     |                                       |                                       |                       |
| Ramp discharge   | Option                                     | Option              | Option                                | Option                                | Option                |
| <b>MONITORS</b>  |  |                     |                                       |                                       |                       |
| ELC+   | Base                                       | Base                | –                                     | –                                     | –                     |
| BaleTrak +   | –  | –                   | Base                                  | Base                                  | Base                  |
| <b>TYRES</b>   |  |                     |                                       |                                       |                       |
| Tyre size  | 11.5/80-15.3                               | 11.5/80-15.3        | –                                     | –                                     | –                     |
|  | 15/55-17                                   | 15/55-17            | 15/55-17                              | 15/55-17                              | –                     |
|  | 19/45-17                                   | 19/45-17            | 19/45-17                              | 19/45-17                              | 19/45-17              |
|  | –  | –                   | 500/50-17 Flotation +                 | 500/50-17 Flotation +                 | 500/50-17 Flotation + |
| <b>WEIGHT</b>  |  |                     |                                       |                                       |                       |
| (max weight with full consumables & options except brakes) | 2600 to 3400 kg                            | 2600 to 3400 kg     | 2900 to 3700 kg                       | 2900 to 3700 kg                       | 2900 to 3700 kg       |

| <b>BALE</b>  |                                       | <b>744</b>                            |                                       | <b>744 Premium</b>    |                       |
|--|---------------------------------------|---------------------------------------|---------------------------------------|-----------------------|-----------------------|
| Diameter (m)   | 1.25 – 1.35                           | 1.25 – 1.35                           | 1.25 – 1.35                           | 1.25 – 1.35           | 1.25 – 1.35           |
| Width (m)  | 1.17                                  | 1.17                                  | 1.17                                  | 1.17                  | 1.17                  |
| Volume (m <sup>3</sup> )                                   | 1.34                                  | 1.34                                  | 1.34                                  | 1.34                  | 1.34                  |
| <b>PICK-UP</b>   | 2 m MaxiCut 14                        | 2.2 m MaxiCut 25                      | 2.2 m MaxiCut 25                      | 2.2 m MaxiCut 25      | 2.2 m MaxiCut 25      |
| Outer width (m, between flares)                            | 2                                     | 2                                     | 2                                     | 2                     | 2                     |
| Power Requirements (kW/hp)                                 | 89/120                                | 89/120                                | 89/120                                | 89/120                | 89/120                |
| Roller Baffle  | Option                                | Option                                | Option                                | Base                  | Base                  |
| Standard gauge wheels                                      | Base                                  | Base                                  | Base                                  | Base                  | Base                  |
| Pivoting gauge wheels                                      | Option                                | Option                                | Option                                | Option                | Option                |
| <b>FEEDING SYSTEM</b>                                      |                                       |                                       |                                       |                       |                       |
| Precutter  | 14 Knives                             | 14 Knives                             | 14 Knives                             | 25 Knives             | 25 Knives             |
| Minimum theoretical Cutting length (mm)                    | 70                                    | 70                                    | 70                                    | 40                    | 40                    |
| Knife selection  | Option 0, 7, 7, 14                    | Option 0, 7, 7, 14                    | Option 0, 7, 7, 14                    | Base 0, 7, 12, 13, 25 | Base 0, 7, 12, 13, 25 |
| Unplugging device  | Pivoting drop floor                   | Pivoting drop floor                   | Pivoting drop floor                   | Pivoting drop floor   | Pivoting drop floor   |
| <b>BALE CHAMBER</b>  |                                       |                                       |                                       |                       |                       |
| Type   | 17 rolls                              | 17 rolls                              | 17 rolls                              | 17 rolls              | 17 rolls              |
| Automatic drive chain lubrication                          | Base                                  | Base                                  | Base                                  | Base                  | Base                  |
| Central greasing banks                                     | Base                                  | Base                                  | Base                                  | Base                  | Base                  |
| <b>BALE CHAMBER DRIVE</b>                                  |                                       |                                       |                                       |                       |                       |
| 540 rpm @ 2000 N.m   | Base                                  | Base                                  | Base                                  | –                     | –                     |
| 1000 rpm @ 1300 N.m  | Option                                | Option                                | Option                                | Base                  | Base                  |
| Powerdrive increased greasing interval PTO                 | X only w/ 1000 rpm @ 1300 N.m gearbox | X only w/ 1000 rpm @ 1300 N.m gearbox | X only w/ 1000 rpm @ 1300 N.m gearbox | Base                  | Base                  |
| <b>TWINE BINDING SYSTEM</b>                                |                                       |                                       |                                       |                       |                       |
| Type   | Two arms                              | Two arms                              | Two arms                              | Two arms              | Two arms              |
| Storage 10 twine balls                                     | Option                                | Option                                | Option                                | Option                | Option                |
| <b>NETWRAP</b>   |                                       |                                       |                                       |                       |                       |
| Type   | CoverEdge                             | CoverEdge                             | CoverEdge                             | CoverEdge             | CoverEdge             |
| <b>BALE UNLOADING</b>                                      |                                       |                                       |                                       |                       |                       |
| Steep slope kit  | Option                                | Option                                | Option                                | Option                | Option                |
| Rubber mat   | Option                                | Option                                | Option                                | Option                | Option                |
| <b>MONITORS</b>  |                                       |                                       |                                       |                       |                       |
| VTI 1300   | Base                                  | Base                                  | Base                                  | Base                  | Base                  |
| <b>TYRES</b>   |                                       |                                       |                                       |                       |                       |
| <b>Tyre size</b>   | 15/55-17                              | 15/55-17                              | 15/55-17                              | –                     | –                     |
|  | 19/45-17                              | 19/45-17                              | 19/45-17                              | –                     | –                     |
|  | 19/45-17 Flotation +                  | 19/45-17 Flotation +                  | 19/45-17 Flotation +                  | 19/45-17 Flotation +  | 19/45-17 Flotation +  |
| <b>WEIGHT</b>  |                                       |                                       |                                       |                       |                       |
| (max weight with full consumables & options except brakes) | 5300 to 6150 kg                       | 5300 to 6150 kg                       | 5300 to 6150 kg                       | 5530 to 6340 kg       | 5530 to 6340 kg       |