

Specifications

TECHNICAL DATA	CLUB H 468.4 DT BASSO		CLUB H 478.4 DT	
	ENGINE			
HÜRLIMANN		1000.4 W		1000.4 W
Cylinders/Displacement	no/cm³	4/4000		4/4000
Max. power (ECE R24.03)	KW/HP/rpm	51.5/70/2350		59/80/2500
Cooling system		liquid / oil		liquid / oil
Unit injection pumps		•		•
Vertical exhaust silencer		•		•
Horizontal silencer with side exhaust		•		—
Fuel tank capacity	litres	70		70
TRANSMISSION				
Synchro gearbox and shuttle		•		•
5-speed gearbox, 20 FWD + 20 REV with creeper		•		•
40 FWD + 40 REV with DRIVE POWER and creeper		○		—
40 km/h gearbox		•		•
Forced transmission lubrication		•		•
P.T.O. clutch with hydraulic servo control		•		•
Rear P.T.O.: 540/1000 rpm		•		•
Rear P.T.O.: 540/1000/540ECON/1000ECON rpm		○		—
Ground speed P.T.O. with independent shaft		•		•
INTEGRATED front P.T.O. with pushbutton operated electrohydraulic control (1000 rpm)		○		○
BRAKES AND STEERING				
Hydrostatic braking on all 4-wheels		•		•
Hydrostatic steering with tilt-adjustable steering column		•		•
FRONT AXLE				
Front differential lock		•		•
Steering angle of 50°		•		•
HYDRAULIC LIFT SYSTEM				
Max. lifting capacity	kg	3450		3450
Pump capacity	l/min	35		35

• = Standard ○ = Optional

TECHNICAL DATA	CLUB H 468.4 DT BASSO		CLUB H 478.4 DT	
	Hydraulic spool valves	n° of ways	4/6	
INTEGRATED front lift. Lifting capacity: 1500 kg		○		—
DRIVING POSITION				
Instrument console with Check Panel		•		•
Suspended pedals and lateral gear levers		•		•
ROPS frame		•		•
Folding ROPS frame		•		—
TYRES				
11.2 R 24 front	14.9 R 30 rear	•		—
14.9 R 24 front	16.9 R 34 rear	—		•
12.4 R 24 front	16.9 R 30 rear	○		○
12.4 R 28 front	13.6 R 38 rear	○		○
300/70 R 20 front	420/70 R 24 rear		•	—
Front fenders + rear fender extensions		•		•
DIMENSIONS AND WEIGHTS (with rear tyres)		14.9R30	420/70R24	16.9R30
Max. length without links	mm	3635	3515	3635
with links	mm	3905	3895	3905
Width: min.	mm	1940	1875	1940
max.	mm	2040	1995	2040
Max. height at hood	mm	1450	1310	1450
at steering wheel	mm	—	1350	—
at ROPS	mm	2400	2250	2400
Ground clearance	mm	400	310	400
Wheelbase	mm	2245	2245	2300
Front track width min.	mm	1500	1570	1500
max.	mm	1630	1650	1630
Rear track width: min.	mm	1500	1500	1500
max.	mm	1600	1620	1600
Min. turning radius with brakes	mm	2800	2800	2800
without brakes	mm	4150	4150	4150
Weight with ROPS	kg	2900	2560	3150
GROUND SPEEDS Speeds in km/h at max. power rpm				
DRIVE POWER transmission 40 FWD + 40 REV	70/80 HP		70 HP LOW	
	FWD	FWD LOW	FWD	FWD LOW
5 SR	1.34	1.15	1.11	0.96
5 L	3.76	3.22	3.13	2.69
5 N	11.97	10.26	9.98	8.56
5 V	36.24	31.06	30.22	25.90
	40.00 (*)		33.00 (*)	

LOW = DRIVE POWER SR = CREEPER L = SLOW N = NORMAL V = FAST (*) EFFECTIVE MAX. SPEED



Hürlimann

Headquarters: Viale F. Cassani, 15 - 24047 Treviglio (BG) Italy - Tel. +39 0363 4211
www.hurlimann.com

Published by the Marketing and Advertising Dept., Code 308.8104.3.3 - 07/2003 I.P.

Akros SPECIALISED LUBRICATION FOR HÜRLIMANN



Technical data and illustrations are guideline only. As our aim at HÜRLIMANN is to deliver a product that increasingly satisfies customer requirements, we reserve the right to update this information at any time, without notice.