

C2R

RECIRCULATING CONE CRUSHER

The McCloskey™ C2R recirculating cone crusher combines the productivity of the 38" cone with the versatility of a full screening and recirculating system, allowing operators to produce a high quality crushed and screened final product with one machine.

The C2R distinguishes itself as an entry-level cone with full level features like an anti-spin system, load and material level monitoring, fully hydraulic push button CSS adjust and full hydraulic relief system. The 5x10 High Energy Screenbox allows greater control over the final product.



RECIRCULATING SYSTEM

Recirculation conveyor allows operators to produce a crushed and screened final product with one machine.



RECIRCULATION SCREEN

5 X 10 High Energy Screenbox has a user-friendly wedge system for faster screen change

MAGNET

Reversible magnet enables material separation from the source material.



FEEDER

Steel hopper with adjustable feed rate via control panel, remote control or fully automatic regulation with feedback from the cone

Engine	350 Hp (261 kW) - 360 Hp (268 kW)
Cone	MC200
Feed Opening	38" (914mm)
Feeder Belt Width	42" (1050mm)
Hopper Volume	6.2m ³ (8.1yd ³)
Crusher Drive	Direct Drive
CSS Adjustment	Hydraulic
Transport Height	11' - 2" (3.4m)
Transport Length	60' - 9" (18.52m)
Transport Width	11' - 5" (3.49m)
Weight	114,640 lb (52,000kg) (est.)
Stockpile Height - Main Conveyor	13' - 10.8" (4281mm)
Main Conveyor Belt Width	48" (1200mm)