

# Q 90 | 100 | 110



- **LOW CENTRE OF GRAVITY FOR MAXIMUM TRACTION AND ADHERENCE TO THE GROUND**
- **VERSIONS WITH SUPER “LOW PROFILE” CAB (JUST 174 CM HIGH)**
- **DRIVING COMFORT: PLATFORM ON “SILENT BLOCK” WITH VARIABLE VISCOSITY**
- **MORE VERSATILE THAN AN ISODIAMETRIC TRACTOR, WITH BETTER PERFORMANCE THAN A CRAWLER AND SUPERB ROAD HANDLING**
- **PREFECT WEIGHT DISTRIBUTION**

## 🎯 A class apart

When it comes to tractors, Q really is a class apart, and is unmatched by any other solution on the market. The aggressive, sloping design of the chassis, the reduced steering radius, the four large drive wheels (which are almost isodiametric) and the powerful engine make the Q the ideal machine for working in orchards and vineyards where limited heights and reduced room to manoeuvre can be challenging, as well as on steep and sloping terrain in general. The compact load-bearing structure, with 50% of the weight distributed on the front axle and 50% on the rear, keeps the centre of gravity low and near the centre of the machine. It also enables maximum traction to be transferred to the ground for safe operation even when working with heavy implements on extreme slopes.

## TECHNICAL FEATURES

### ENGINE

VM 4 Cyl Tier IIIB  
Q 90: 59 kW / 80 HP  
Q 100: 67 kW / 91 HP  
Q 110: 75 kW / 102 HP  
DPF + IGR

### TRANSMISSION

24+12 transmission with 4 gears across 3 ranges + underdrive (20%)  
Mechanical Reverse Shuttle  
4WD and electro-hydraulic DIFF-lock

### HYDRAULIC

Lifting capacity 2500 kg  
Electronically controlled lift (optional)  
Pump output 100 l/min (39+6l), open-centre up to 3 rear mechanical distributors up to 3 front electro-hydraulic distributors

### DRIVER AREA

Pressurised platform / cab

### DIMENSIONS

Wheelbase: 1923 mm  
Weight: 2275 kg (Plat)  
Tyre: 420/65R20  
Width (min-max): 1591-1876 mm