



RC50

Single drum soil compactors



Clear view of the work area and simple operation: RC50

A perfect view in all directions makes working with the Wacker Neuson single drum soil compactors safer and more comfortable. Thanks to the compact design and specially shaped engine hood, the operator always has the work area and the drum in view from his seat. The simple operation via an intuitively designed display and joystick also make work easier and ensure that the operator is familiar with the machine in no time.

- 3-point articulated joint for optimal driving comfort
- Adjustable and rotatable operator's seat and simple operation via the joystick
- The simplest maintenance and long service intervals
- Maximum gradeability due to the innovative drive concept and generous angle of slope
- 2 model versions: with smooth drum or with sheepfoot drum

Two types of drums:

Optionally with a smooth drum or sheepfoot drum

Single drum soil compactors with a smooth drum	RC50
Single drum soil compactors with a sheepfoot drum	RC50p



Master up to a 60% gradient
thanks to the wheel motors.

- Drive system via hydraulically activated wheel motors
- Distribution of the torque to the front and rear axle depending on the requirements
- Compaction on slopes and driving in steep trench applications is no problem



Compaction through vibration
Vibration for high compaction depth.
RC50 and RC50p

Technical specifications

	RC50	RC50p
Operating data General		
Operating weight with roll-over protective structure kg	4,815	4,935
Operating weight with cabin kg	5,035	5,155



	RC50	RC50p
Operating weight max. kg	5,710	5,530
Drum type	smooth/undivided	Sheepsfoot
Dimensions		
L x W x H mm	4,040 x 1,500 x 2,867	4,040 x 1,500 x 2,867
Drum width mm	1,370	1,370
Drum diameter mm	1,000	1,155
Operating width mm	1,370	1,370
Ground clearance Middle mm	270	270
Axle load Front kg	2,625	2,745
Axle load Rear kg	2,410	2,410
Curb clearance left/right mm	65	65
Turning radius mm	3,375	3,375
Operating data Vibration		
Centrifugal force kN	69	69
Frequency Hz	30	30
Amplitude mm	1.55	1.45
Linear force static, front N/mm	19.2	20
Travel speed Operation, max. km/h	6	6
Travel speed Transport gear, max. km/h	12.5	12.5
Gradeability with vibration %	55	55
Gradeability without vibration %	60	60
Engine / Motor		
Engine / Motor type	4-cylinder diesel engine, V3307-CR-T	4-cylinder diesel engine, V3307-CR-T
Engine / Motor manufacturer	Kubota	Kubota
RPM / speed rpm	2,200	2,200
Operating performance kW	54.6	54.6
Traction drive	hydrostatic with wheel motor	hydrostatic with wheel motor
Tank capacity l	123	123



**WACKER
NEUSON**
all it takes!

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2016 Wacker Neuson SE.