

S 90 | 100 | 110

S 90 | 100 | 110 GT

- HYDRAULIC CIRCUIT FLOW RATE 39+61 LITRES

- OPTIMAL WEIGHT DISTRIBUTION

- MAXIMUM VERSATILITY:
S - EASY TO HANDLE AND AGILE
S GT - ROBUST AND COMPACT

- DRIVING COMFORT: PLATFORM ON "SILENT BLOCK" AND "PRESSURISED" CAB WITH A/C



May the force be with you

A "compact" tractor for orchards and vineyards that boasts more than 100 horsepower? Operators who choose the S Series (with turbo intercooler, four wheel drive, platform on silent-block suspension or cab with panoramic view and air conditioning) will not miss having a bigger machine. Perfectly balanced, compact and tough, it offers tireless performance, and is the ideal companion for stress-free operation: available in 6 versions, so you can choose EXACTLY the right model for you.

TECHNICAL FEATURES

ENGINE

VM 4 Cyl Tier IIIB
S 90: 59 kW / 80 HP
S 100: 67 kW / 91 HP
S 110: 75 kW / 102 HP

DPF + IGR

TRANSMISSION

24+12 transmission with 4 gears across 3 ranges + underdrive (20%)

Mechanical Reverse Shuttle

4WD and electro-hydraulic DIFF-lock

HYDRAULIC

Lifting capacity 2500 kg
Electronically controlled lift (optional)
Pump output 100 l/min (39+61), open-centre up to 3 rear mechanical distributors up to 3 front electro-hydraulic distributors

DRIVER AREA

Pressurised platform / cab

DIMENSIONS

Wheelbase: 1973 mm / 1990 GT version

Weight: 2375 kg (Plat)

Tyre: 360/70R24 / 360/70R28 GT version

Width (min-max): 1404-1830 mm