

WL 48 Wheel Loader 4,8 t

Item Number: 0610146

WL 48

Robust workers

>> The WL 48 and WL 50 wheel loaders from Wacker Neuson, with their high-performance 4-cylinder Deutz engines, day-to-day execute an enormous workload. These agile and versatile machines are strong reliable helpers at any construction site and are ideally suited for a variety of jobs. In addition they are extremely frugal in consumption and easy to maintain. Their bright, friendly cabs are roomy, comfortable and offer excellent 360° visibility. Very soon you won't want to part with these robust workers. <<



Additional Advantages

- Inspections can quickly and easily be carried out. Simply tilt the cab and all the important components are already accessible.
- The fully spring-mounted, height adjustable, ergonomically shaped comfort seat with safety belt ensures operator-friendly posture.
- The multi-function lever: Change of direction, lift movements or the tipping in and out of working tools can be controlled with one hand.
- Fast changes: Thanks to the hydraulic quick change system, the add-on equipment is easily exchanged.
- The ROPS and FOPS tested cab offers safety, freedom of movement and good 360° visibility. Heater and fan work efficiently and quietly and keep all windows free of fog and ice. This keeps everything in view in every situation.
- The large volume air filter with interior safety cartridge guarantees a long service life for the 4-cylinder Deutz engine. Contaminated air cannot reach the engine.
- The compact wheel loaders develop enormous biting forces through the Z-kinematics. Tons of material can be moved effortlessly - placed exactly on target.
- High stability against overturning due to the low machine center of gravity and good load distribution.

Description	Metric	Imperial
Motor type	Deutz (F4M 2011)	
Power	42,5 kW	- PS
Speed	2.300 1/min	- rpm
Speed	0 - 20 km/h	- mph
Operating weight	4.835 kg	- lb
Shovel capacity	0,75 m ³	- ft ³
Overall length with standard shovel	5.421 mm	- in
Total width, standard	1.840 mm	- in
Height of cab	2.598 mm	- in
Total working height	4.088 mm	- in
Max. height of bucket pivot point	3.332 mm	- in
Inside turning radius	1.667 mm	- in
Max. lifting force	4.342 kg	- lb
Tipping load with bucket	3.116 kg	- lb
Tipping loads with bucket (articulated)	2.544 kg	- lb
Tipping loads with pallet fork (straight)	2.589 kg	- lb
Tipping loads with pallet fork (articulated)	2.116 kg	- lb
Breakout force	3.431 daN	- lb
Height over bar	- mm	- in

Standard Package - WL 48

includes operator's manual and parts book

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Thursday, March 22, 2012

