

ZOOMLION ARTICULATING BOOM LIFTS

Comply with CE/ANSI/GB Standard

HIGHLIGHTS

ZA20JE GB

- Provide a work height of 21.45 m and lift capacity of 250 kg.
- Fast lift system directly lowers the boom from the highest position to the ground without folding the boom.
- Accurate and efficient traveling AC drive system and on-board motion AC drive system provide strong power stable control and maintenance-free motor.

ZA20JE CE

- Provide a work height of 21.50m and lift capacity of 250 kg.
- Fast lift system directly lowers the boom from the highest position to the ground without folding the boom.
- Accurate and efficient traveling AC drive system and on-board motion AC drive system provide strong power stable control and maintenance-free motor.
 - Independent auxiliary power system for more secure applications.

NEW

FEATURES

Standard Features

Proportional control
All motion alarm
Flashing amber beacon
Self-closing entry gate
Emergency descent system
Emergency stop button
Auto-leveling system
On-board diagnostic system
Over tilt protection system
Oscillating axle
Load sensing system
4.3' LED display
Horn

Accessories & Options

AC power to platform
Airline to platform
2.44x0.91m work platform
Non-marking tire



ACCESS WITH ZOOMLION GREEN

Hotline: +86 400-800-0157
E-mail: awm@zoomlion.com

Add: ZOOMLION Wangcheng Industrial Park, Tengfei Road 997, Changsha, Hunan, China.
Learn more at <http://en.zoomlion.com/>

ELECTRIC ARTICULATING BOOM LIFTS

Comply with CE/ANSI/GB Standard

| Model | ZA20JE GB | ZA20JE CE |
|--------------------------|---------------------------------|----------------------------------|
| Size | | |
| Work Height | 21.45m | 21.50m |
| Platform Height | 19.45m | 19.50m |
| Horizontal Outreach | 11.45m | 11.45m |
| Up and Over Height | 8.25m | 8.30m |
| A - Stowed Length | 8.72m | 8.72m |
| B - Stowed Width | 2.49m | 2.49m |
| C - Stowed Height | 2.52m | 2.56m |
| D - Platform Length | 1.83m | 1.83m |
| E - Platform Width | 0.76m | 0.76m |
| F - Wheelbase | 2.52m | 2.52m |
| G - Ground Clearance | 330mm | 375mm |
| Performance | | |
| Platform Capacity | 250kg | 250kg |
| Drive Speed | 6.1km/h | 6.1km/h |
| Gradeability | 45% | 45% |
| Axles Oscillation | 200mm | 200mm |
| Turning Radius (Inside) | 2.78m | 2.78m |
| Turning Radius (Outside) | 5.49m | 5.49m |
| Swing | 400°non-continuous | 360°continuous |
| Platform Rotation | ±90° | ±90° |
| H-Tail Swing | 0.6m | 0.6m |
| Max. Working Slope | 3/5° | 3/5° |
| Max. Wind Speed | 12.5m/s | 12.5m/s |
| Power | | |
| Battery | 8×6V/420Ah | 8×6V/420Ah |
| Charger | 48V/35A | 48V/60A |
| Drive Motor | AC 32V/3.3kw | AC 32V/3.3kw |
| Lift Motor | AC 32V/10kw | AC 32V/10kw |
| Auxiliary Power | Manual Pump | 12V DC |
| Hydraulic Tank Capacity | 75L | 75L |
| Tire | | |
| Type | 33×12 D610 Foam-filled Tires | 355/55 D625 Foam-filled Tires |
| Weight | | |
| Gross | 9200kg | 9200kg |

